

Rough Terrain Forklift

Used Rough Terrain Forklift Simi Valley - Broadly defined, a forklift truck uses two forks to load, transport and unload material. Forklifts fall into two main categories, industrial forklifts and rough terrain forklifts. The first category of forklifts, industrial forklifts, are mostly used in warehouses and at loading docks on surfaces that are relatively smooth and level. Ideal for uneven terrain and rocky locations, rough terrain forklifts travel well in difficult environments. Commonly found at exterior construction sites, rough terrain forklifts have the tires, size and weight capacity to handle heavy loads. The main difference between industrial and rough terrain forklifts is that industrial forklifts are fitted with cushion tires, a common, over-the-road type tire. Rough terrain models rely on pneumatic tires, a kind of tractor tire known for better floatation and traction abilities. Internal combustion engines can power industrial forklifts; however, more often they rely on an electrical source such as a fuel cell or better. Rough terrain models typically rely on an internal combustion engine. Types of Class 7 Rough Terrain Forklift Trucks There are three main types of Class 7 Rough Terrain Forklift Trucks: 1. Straight mast forklifts; 2. Telehandler forklifts; and 3. Rotating telehandler forklifts. Every rough terrain forklift truck is designed to operate on disturbed ground and difficult locations commonly found in military and construction atmospheres. A rough terrain forklift also offers increased maneuverability and performance. Safety considerations are taken into account for rough terrain locations with raising loads in difficult environments to keep the operator safe from tipping over. For safety reasons, it is vital the forklift maintains stability before moving, lifting or lowering. Stability of ground and knowledge of proper lifting technique is essential for safe operation of rough terrain forklifts.

Straight Mast Forklifts Designed to facilitate safe transport along difficult terrain such as demolition sites and construction locations, straight mast forklifts can complete the job safely and efficiently. Pneumatic cushion tires allow this forklift better maneuverability and accessibility around difficult terrain. Pneumatic tires allow the machine to successfully traverse difficult terrain. It is common for straight mast forklifts to come with 2-wheel or 4-wheel drive. Even though these machines are better utilized in exterior locations, many straight mast forklifts operate with propane or diesel, enabling them to be used indoors for short timeframes. The lift capacities of straight mast forklifts are similar to most standard forklifts with a range of approximately 5,000 to 36,000 pounds.

Telehandler or Telescopic Handler Forklifts Telescopic handler forklifts or telehandlers feature a telescoping boom; hence their name. This telescoping boom allows the forklift truck to pick up and place loads at various distances and lift heights in front of the machine. Better reachability delivers greater flexibility to the forklift operator while placing loads. A standard telehandler forklift is long and low, with two wheels at the very front of the forklift and another pair of wheels toward the rear of the machine. The telescopic boom can be found at the back of the forklift, mounted on a pivot that is attached many feet higher than the frame of the unit. The left side of the machine houses the cab and the hydraulic fluid tank and the fuel tank are found opposite to the cab. Within the frame itself, the transmission and engine are located along the center-line of the forklift. Creating a balanced machine is essential for a well-designed forklift. Having this particular configuration generates a stable environment for lifting, lowering and transporting loads. Compared to standard forklifts, telehandlers deliver higher lift heights. Otherwise known as high-reach telehandlers or compact telehandlers, these models perform. Compact telehandlers can extend their full load capacity from eight-teen feet and the high-reach models to fifty-six feet. Their load capacities usually range between 5,500 and 12,000 pounds. All-terrain forklifts rely on all-wheel steering to deliver better maneuverability and stability. The power-shift transmission and steering features allow the operator to move the forklift into a safe and successful working proximity. The latest telehandler models feature ergonomic upgrades for ultimate operator comfort. These features include tilted steering options and roomier cabs to increase operator comfort. Increasingly, these types of ergonomic features are in demand at worksites as they have been shown to improve productivity by decreasing operator

repetitive stress injuries and operator fatigue. Most telehandler forklifts rely on a single joystick. The joystick controls all the forklift's boom functions as well as the hydraulic system which allows for straightforward and efficient operation. These machines can use non-marking tires to allow them to be suitable for maintenance in stadiums and on buildings or billboards and sign operations. Rotating Telehandler or Roto Telescopic Handler Forklifts Rotating telehandler or roto telescopic handler forklifts have many features in common with the standard telehandler forklift. These include the rotating telehandler's ability to lift heavy weight to great heights. This unit's added turntable and rotation flexibility increases the types of jobs it can complete. The rotating function allows the forklift to swivel a full 360 degrees around, enabling access a much larger work area without having to reposition the forklift. Because of this additional feature, rotating telehandlers often have a second joystick to allow operation of the rotation function apart from the lift function. Useful additional features may be added to your standard telehandler or rotating telehandler including 4WD, increased traction via minimized slip differential on the rear axle, and power-assist steering. Of course, a machine that can rotate has extra safety considerations to understand. Rotating telehandler rough terrain models come with standard stabilizers to establish more safety while rotating loads back and forth. Certain rotating telehandlers operate without stabilizers; minimizing the time it takes to reposition the machine and move to other workplace locations. Rotator telehandlers are usually smaller than their fixed cab counterparts, the standard telehandler. Because of this, their load capacities are also smaller than the standard telehandler. Ranging between four thousand and ten thousand pounds, rotating telehandlers can reach lift heights from 15 to 80 feet. Both telehandlers and rotator telehandlers can be used as a crane when fitted with a winch attachment. These units can enable job sites that require a crane to get the job done without having to rent and transport a separate machine. Advancements for Rough Terrain Forklifts Numerous attachments can be found for rough terrain forklifts including articulating booms, rotating fork carriages, booms, winches and similar items. Forklift attachments are vital for diversifying the machine. They will continue to be developed for years to come. The majority of advancements will be delivered as safety features built to enhance the rough terrain models. Some new safety features have already been developed such as automatic load restriction devices. These systems automatically weigh a load and then calculate the safe reach distance of that load, taking into consideration the angle and extension of the boom. An alarm will go off once the safe distance is reached. This alerts the operator that immediate adjustments need to be made to the boom angle, reach distance or load weight.